



# NIPPON PAINT

# KLEANWALL

Fungicidal Solution

Walltron Kleanwall is recommended for highly infested interior and exterior walls to prevent further growth of algae and fungi.

## GREEN ASSURED



## PRODUCT FEATURES



**Enhance Performance of Topcoat**



**Inhibits the growth of algae and fungi**



**Economical**

## APPLICATION AREA:

It can be used on all types of exterior and interior walls that are susceptible to algal and fungal growth. It can be used on both old or new construction.





**NIPPON  
PAINT**

**KLEANWALL**  
Fungicidal Solution

## TECHNICAL DETAILS

Dilution: Ready to use ( No dilution)

### Coverage:



#### WALLTRON KLEANWALL

100-110 sq.ft/coat.

Coverage depends on porosity of substrate.

## HOW TO APPLY

### Surface Preparation:



- Clean the surface till it is free from dust, grease and flaking paint.
- Any unstable paint, algae and fungi on the wall to be removed, by using high-pressure wash or coir brush.
- Apply one coat of Kleanwall with brush and allow drying for minimum 4-6 hrs.
- After complete drying apply second coat of the Kleanwall,
- After an interval of 4-6 hrs apply primer followed by Nippon emulsion paint.

### Precautions:

- Stir well and strain before use.
- Do not use on wet surfaces or when it rains.
- Do not dispose of excess material over natural vegetation.
- Do not thin.
- Avoid painting when the temperature is below 10° C. Painting is not recommended if the moisture content and alkalinity of the walls is high.

## SAFETY AND ENVIRONMENT

#### During Painting:

Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.

#### Cleaning:

Wash all the tools with water immediately after application.

#### Safety Instructions:

In the case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint from skin, use soap and water or appropriate cleanser. May be harmful if swallowed. In case of ingestion seek immediate medical attention. In the event of spillage, contain and collect spilt paint by using sand or earth.

#### Storage:

Store paint in a cool, dry and well ventilated place away from heat sources, flammables or direct sunlight. Keep container tightly closed in a secure, upright position. Do not store near food, drink or animal feed. Keep out of reach of children. Do not dispose of unwanted paint into drains, water sources or open sewers.

#### Environment:

Does not contain any added lead, mercury or chromium compounds.

#### Shelf Life:

1 Year from the date of manufacture in original tightly closed container.

