

PIPE BOND - CPVC SOLVENT CEMENT



EXCELLENT ADHESION, FAST SETTING WATERPROOF BONDING.

Description

It is a high-strength, fast setting solvent cement specifically designed for all types of CPVC pipes and fittings. Its medium-bodied, yellow formulation ensures a secure and durable bond.

Application

It is designed for a wide range of CPVC plastic pipe applications, specially formulated for CPVC or PVC industrial piping systems which requires chemical resistance to acids, bases, caustics, hypochlorite solutions, water and aqueous salt solutions.

Available Pack Sizes

50ml, 100ml

Directions

Directions to Use:

- Surface must be clean, dry and free from dust grease, oil or water.
- Roughen matting surface to the full depth of socket using medium glass paper or emery cloth.
- Apply the solvent cement to both surfaces to be bonded with a dry, clean brush to give uniform coating.
- It will dissolve and soften the surfaces of the pipes and fitting. Assemble while cement is wet.
- When the pipes and fittings are assembled together, the soften surfaces mix and on hardening produce a chemically welded joint.
- Hold firmly for 30 sec to allow initial bonding, then remove surplus solvent cement and should not be disturbed for 15 min.

Safety and First Aid Directions

Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to the nervous system through prolonged or repeated exposure by inhalation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe fumes. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection. Store in a well-ventilated place. Keep cool. Store locked up. Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.

Directions

Highly flammable ,keep away from heat source or naked flame. Store in a dry and and cool place with temperature below 30°C

Danger



Shelf life

2 Years.



NIPPON PAINT (INDIA) PRIVATE LIMITED
129, 140, 9th Floor, Prestige
Palladium Bayan Building,
Greens Road, Thousand
Lights, Chennai- 600006,
Tamil Nadu, India
Toll-Free: 1800 425 3636
www.nipponpaint.co.in

Disclaimer:

The product information and application details we provide are in good faith and are meant to serve as a general guideline for usage. We advise users to conduct tests and trials to ensure that our products meet their requirements before full-scale usage. Since factors such as the correct identification of problems, quality of other materials used, and on-site workmanship are beyond our control, we cannot provide any expressed or implied guarantee or warranty regarding the results obtained. We do not assume any liability or consequential damage for unsatisfactory results arising from the use of our products.