



Colour-lock technology



Excellent Coverage



Dirt Pick-up Resistant



Anti-algal



Water Resistance

8

Years Warranty*



Heat Ban Technology



Quartz Technology



THE 8 REVOLUTION

Introducing Weatherbond 8,
best-in-class exterior emulsion with 8
power packed features



NO. 1 PAINT IN ASIA PACIFIC*

*T&C apply

PRODUCT DESCRIPTION :

Nippon Paint Weatherbond 8 is a specially formulated acrylic based high performance exterior emulsion paint with **Quartz Technology** providing twice the toughness and durability resulting in supreme protection against harsh weather. It imparts a rich sheen finish and provides better anchoring and water resistance. It has anti-algal and dirt pick resistance to keep your walls fresh for longer time.




PRODUCT FEATURES & BENEFITS :



DIRT PICKUP RESISTANT

- The exteriors look new and beautiful for years
- It doesn't allow dirt/dust to settle on wall



HEAT BAN TECHNOLOGY


- The innovative Heat Ban technology reflects back 90 % of the sunrays which reduces surface temperature up to 5°C
- This makes the interior cooler, thus helping to save energy used for Air conditioning



Low VOC

LOW VOC

- It does not emit air polluting harmful vapours and paint odour that pollutes our environment
- Environment friendly and Healthy paint



ANTI-ALGAL

- Weatherbond 8 is resistant to algae / fungus



QUARTZ TECHNOLOGY

- Hard and tough paint film
- It Provides excellent Water resistance, UV radiation and dirt penetration



WATER RESISTANCE

- Prevents water to enter the walls hence forbidding algal or fungal growth
- Beautiful looking exteriors for long



COLOUR-LOCK- TECHNOLOGY

- Weatherbond 8 Keeps the walls looking beautiful for a long time



Excellent Coverage

- This Product yields excellent coverage which might help save the total cost

- * **8 years Performance Warranty for Film Integrity, Flaking, Peeling & Colour Retention**
- * **5 years Anti Algal warranty. Please refer Warranty Card for further details**

Where to Use : It Can be used on Exterior Masonry Surfaces

International quality, hi-tech paints

1800 425 3636 8939 65 3636

PRODUCT TECHNICAL INFORMATION :



| | |
|----------------------------------|--|
| Bases | • White & Bases |
| Colour Range | • Please refer to Nippon Paint shade card and fan decks |
| Finish | • Rich Sheen finish |
| Coverage | • 110 - 130 sq.ft/litre/coat & 55 - 65 sq.ft/litre/2 coats (Actual coverage is dependant on the substrate Condition, surface porosity, method of application) |
| Dry Time | • To Touch: 30 minutes / To Recoat: 4-6 Hours |
| Gloss Level | • 60° head: 10 to 20 units |
| Clean Up Solvent | • Clean, potable water |
| Stability of Dilute Paint | • 24 Hours |
| Shelf Life | • 3 Years from the date of manufacture in original tightly closed containers |
| Dilution | • 40-50% by volume with clean, potable water |

Standard Application System :

Before application, read the safety, health and environmental information and the precautions given below

Application Tool

Suitable for application by brush or roller or conventional spray

Surface Preparation :

For Repainting : Clean the surface till it is free from dust, grease and flaking paint from surface. Any unstable paint to be removed, using high pressure wash or scraper whichever is appropriate. Algae And fungus on the wall to be removed, by using high pressure wash or coir brush, it must be treated with Walltron Kleanwall fungicidal solution.

New plaster/Fresh Concrete : Ensure surface is completely cured and dry. Application of cement paint/lime/Cement putty as undercoat is not recommended. Fill the cracks upto 3mm if any with Walltron N-seal crack fill powder.

Recommended Painting System :

Primer

- Nippon Dr. Bond Efflorescence Resistance Sealer
- Nippon Paint Multi-Purpose Wall Sealer/Exterior Primer
- Apply 1 coat and allow to dry for 4-6 hours

Top Coat

- Nippon Weatherbond 8
- Apply 2-3 coats in an interval of 4-6 Hours

Recommended Painting System For Waterproofing & Anticarbonation System :

Base Coat

- Hydroshield Damp Proof
- Apply a coat with 30% dilution using potable water by volume
- Apply a coat without dilution

Top Coat

- Nippon Weatherbond 8
- 2-3 coats with upto 20% dilution with potable water by volume at an interval of 4-6 hours

Note :

For dark shades and Horizontal surface, one or two additional coats are recommended for better performance of paint film. Primed surface should be immediately painted with top coats. For best Performance use Nippon Dr. Bond Efflorescence Resistance Sealer as primer. If surface is applied with cement based putty apply Maxx clear Sealer as primer for superior adhesion.

Safety Health & Environmental Information :

During Painting :

- Always work in a well ventilated area
- Wear appropriate attire, especially gloves and eye protection gear
- Avoid contact with skin as it may cause irritation

Cleaning :

- Wash all the tools with water immediately after application

Safety Instruction :

- In the case of eye contact, rinse immediately with water and seek immediate medical treatment
- To remove paint from skin, use soap and water or appropriate cleanser
- In the event of spillage, contain and collect spilt paint by using sand or earth

Precautions :

- Avoid painting when the temperature is below 10 degrees Celsius
- Painting is not recommended if the moisture content and alkalinity of the walls is high
- Moisture content of the walls should be below 16% (measured by Protimeter) and alkalinity of the wall should be below pH-9
- Relative humidity should be below 85%. Painting on a newly plastered wall is recommended after 12 weeks of curing

Storage :

- Store paint in a cool, dry and well ventilated place away from heat sources, flammables or direct sunlight
- Keep container tightly closed in a secure, upright position
- Do not store near food, drink or animal feed
- Keep out of reach of children
- Do not dispose of unwanted paint into drains, water sources or open sewers
- To dispose safely, pour unwanted paint onto old newspapers and let dry before placing in a proper waste receptacle

Disposal Information :

- Disposal of any paint waste & containers in accordance with applicable Environment (Protection) Act 1986 under the Hazardous Wastes (Management & Handling) rules 1989

Environment :

- Does not contain any added lead, mercury or chromium compounds
- Lead content does not exceed 90 parts per million



Contact Us

Registered Office : NIPPON PAINT (INDIA) PRIVATE LIMITED

Plot No. K-8(I), Phase-II, SIPCOT Industrial Park, Mambakkam Village, Sriperumbudur, Sunguvarchatiram, Kancheepuram – 602 106, Tamil Nadu, India