



NIPPON PAINT MATEX MEDIPLUS

Nippon Paint Matex Mediplus is a premium emulsion specially designed based on unique technology providing all shades with only one base, It delivers excellent coverage & possess good washability. Its anti-bacterial property provides proven protection against bacteria and also contains low VOC ensuring safe and healthy interiors.

GREEN ASSURED



PRODUCT FEATURES



Smooth Matt Finish

Gives the walls a smooth even finish by hiding unevenness



Resistant to Bacteria & Fungus

Keeps the walls hygienic. It reduces the chance of picking up allergies and keeps residents healthy.



Low VOC

Environment-friendly



Excellent Coverage

Lower cost /sft





**NIPPON
PAINT**

**MATEX
MEDI+**
ANTI-BACTERIAL INTERIOR EMULSION

TECHNICAL DETAILS

Bases	:	One Base
Colour Range	:	Please refer to Nippon Paint shade card and fan decks
Finish	:	Smooth Matt
Dry Time	:	To Touch: 30 minutes To Recoat: 4-6 Hours
Gloss Level	:	60° Head: 1-10 units
Clean up solvent	:	Clean, potable water
Stability of diluted paint	:	24 Hours
Shelf life	:	3 Years from the date of manufacture in original tightly closed containers
Dilution	:	50 - 60 % by volume with clean, potable water Stir & Strain well before use Upt0 30% by volume with potable water for dark shades

Coverage:



MATEX MEDIPLUS

220 - 250 ft²/litre/coat &
110 - 130 ft²/litre/2 coats

(Actual coverage is dependant on the substrate condition, surface porosity, method of application).

HOW TO APPLY

Surface Preparation:



Keep surface clean & dry. Remove dust, dirt, grease and any flaking paint from the surface and sand to smoothen. Ensure there is no fungus or moisture on the wall. Repair surface defects with suitable filler.

Application:

Brush:	50 - 60% with clean potable water
Roll:	50 - 60% with clean potable water
Conventional Spray:	60 -70% with clean potable water


Process:



Primer
Nippon Paint
Multi-Purpose
Wall Sealer/
Latex Interior
Primer

Apply 1 coat


Allow it to dry
for 6-8 hours



Putty
Nippon Paint
Acrylic Wall Putty

Apply 1-2 coats


Allow it to dry
for 12-18 hours



Primer
Nippon Paint
Multi-Purpose
Wall Sealer/
Latex Interior
Primer

Apply 1 coat

Allow it to dry
for 6-8 hours



Top Coat
Nippon Paint
Matex Mediplus

Apply 2-3 coats

Allow it to dry
for 4-6 hours

SAFETY AND ENVIRONMENT

During Painting:

Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.

Cleaning:

Clean all equipments with clean water immediately after use.

Safety Instructions:

In the case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint from skin, use soap and water or an appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.

Precautions:

Avoid painting when the temperature is below 10 degrees Celsius. Painting is not recommended if the moisture content and alkalinity of the walls is high. Moisture content of the walls should be below 16% (measured by Protimeter) and alkalinity of the wall should be below pH-9. Relative humidity should be below 85%. Painting on a newly plastered wall is recommended after 12 weeks of curing.

Storage:

Store paint in a cool, dry and well ventilated place away from heat sources, flammables or direct sunlight. Keep container tightly closed in a secure, upright position. Do not store near food, drink or animal feed. Keep out of reach of children. Do not dispose of unwanted paint into drains, water sources or open sewers. To dispose safely, pour unwanted paint onto old newspapers and let dry before placing in a proper waste receptacle.

Disposal Information:

Disposal of any paint waste & containers must be in accordance with applicable Environment (Protection) Act 1986 under the Hazardous Wastes (Management & Handling) rules 1989.

Environment:

Does not contain any added lead, mercury or chromium compounds.

Lead content does not exceed 90 parts per million.

Note: For dark shades and horizontal surfaces 1 or 2 additional coats may be required for better performance of paint film.

Post Application Instruction: Ensure dry dust cleaning at regular intervals for best performance. Allow drying time of atleast 3 weeks before cleaning with mild soap solution using sponge.

