



NIPPON PAINT SUMO XTRA DUST SHIELD

Nippon Paint Sumo Xtra Dust Shield is a specially formulated water based exterior emulsion with colour-lock technology which ensures that the colour looks bright and clean. Its unique water resistant property keeps your exterior walls protected and beautiful for long. Its new improved formula provide very good Dirt Pickup Resistance (DPUR).

GREEN ASSURED



PRODUCT FEATURES



Colour-lock technology

Keeping the walls look beautiful for long



Low VOC

Environment-friendly and healthy paint.



Dirt Pick-up Resistant

Exteriors look new and beautiful for years.



Water Resistance

Resulting in no blistering and peeling of the paint film.



6 Year Protection

*6 years Performance Warranty for Film Integrity, Flaking, Peeling & Colour Retention.





NIPPON PAINT

SUMO XTRA DUST SHIELD

DUST RESISTANT EXTERIOR EMULSION

TECHNICAL DETAILS

Bases	:	White & Bases
Colour Range	:	Please refer to Nippon Paint shade card and fan decks
Finish	:	Smooth Sheen
Dry Time	:	To Touch: 30 minutes To Recoat: 4-6 Hours
Gloss level	:	60° Head: 0-10 units
Clean up solvent	:	Clean, potable water
Stability of diluted paint	:	24 Hours
Shelf life	:	3 Years from the date of manufacture in original tightly closed containers
Dilution	:	40-50% by volume with clean, potable water. Stir & Strain well before use.

Coverage:



SUMO XTRA DUST SHIELD

110 - 130 sq.ft./litre/coat
& 55 - 65 sq.ft./litre/2 coats

(Actual coverage is dependant on the substrate condition, surface porosity, method of application)

HOW TO APPLY

Surface Preparation:

For Repainting: Clean the surface till it is free from dust, grease and flaking paint. Any unstable paint to be removed, using high pressure wash or scraper whichever is appropriate. Algae and fungus on the wall to be removed, by using high pressure wash or coir brush and shall be treated with Walltron Kleanwall fungicidal solution.

New plaster/Fresh Concrete: Ensure surface is completely cured and dry. Application of cement paint/lime/Cement putty as undercoat is not recommended. Fill the cracks upto 3mm if any with Walltron N-seal crack fill powder.

Application:

- Brush
- Roller
- Conventional Spray

Process:



Primer
Nippon Paint
Multi-Purpose
Wall Sealer/
Exterior Primer

Apply 1 coat

Allow it to dry
for 4-6 hours



Top Coat
Nippon Paint
Sumo Xtra
Dust Shield

Apply 2-3 coats

Allow it to dry
for 4-6 hours

SAFETY AND ENVIRONMENT

During Painting:

Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.

Cleaning:

Clean all equipments with clean water immediately after use.

Safety Instructions:

In the case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint from skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.

Precautions:

Avoid painting when the temperature is below 10 degrees Celsius. Painting is not recommended if the moisture content and alkalinity of the walls is high. Moisture content of the walls should be below 16% (measured by Protimeter) and alkalinity of the wall should be below pH-9. Relative humidity should be below 85%. Painting on a newly plastered wall is recommended after 12 weeks of curing.

Storage:

Store paint in a cool, dry and well ventilated place away from heat sources, flammables or direct sunlight. Keep container tightly closed in a secure, upright position. Do not store near food, drink or animal feed. Keep out of reach of children. Do not dispose of unwanted paint into drains, water sources or open sewers. To dispose safely, pour unwanted paint onto old newspapers and let dry before placing in a proper waste receptacle.

Disposal Information:

Disposal of any paint waste & containers in accordance with applicable Environment (Protection) Act 1986 under the Hazardous Wastes (Management & Handling) rules 1989.

Environment:

Does not contain any added lead, mercury or chromium compounds.

Lead content does not exceed 90 parts per million.

Note: For dark shades and Horizontal surface, one or two additional coats are recommended for better performance of paint film. Primed surface should be immediately painted with top coats.
Post Application Instruction: To enhance the performance of the paint film, clean the exterior surface, algae & fungus if any with clean water in an interval of 6 month

