



NIPPON PAINT

N-SEAL

Crack Fill Powder

Walltron N-SEAL Crack Fill Powder is a 1K cement-based polymer-rich powder mix to fill cracks up to 3-5mm thickness on plaster surfaces.

GREEN ASSURED



PRODUCT FEATURES



Pure White



Excellent Bonding



Water-resistant



No shrinkage

APPLICATION AREA:

It is recommended to use for both interior and exterior cracks on horizontal and vertical surfaces upto 5mm thickness.





NIPPON PAINT

N-SEAL

Crack Fill Powder

TECHNICAL DETAILS

Appearance	Free flowing grey powder
Pot life	30 min

Coverage:



WALLTRON N-SEAL CRACK FILL POWDER

Approx 25–30 running m/kg

Coverage depends on size of the crack.

HOW TO APPLY

Surface Preparation:



Crack should be cleaned and loose particles should be removed, small cracks should be opened in V shapes and clean thoroughly.

Precautions:

- Recommended only for filling cracks, not for filling structural joints.
- Do not mix excess water.
- Use the mix within 30 minutes.
- Paste to be applied on static cracks only.

Application:

- Mix Nippon Paint N-SEAL crack fill powder in clean water in the ratio of 2.5:1 (5kg N-SEAL and 2 kg water) stir continuously to get a homogenous lump-free paste.
- Wet the surface slightly before application and allow excess water to drain off. Fill Nippon Paint N-SEAL with putty blade or trowel. Level and smoothen the surface and allow it to dry for 24 hours.
- Use sandpaper if required.

Cleaning:

- Excess cured material can be removed by vigorous scrubbing by sand paper or scraper.
- Clean the tools with clean water before material sets.

SAFETY AND ENVIRONMENT

During Painting:

Always work in a well-ventilated area. Wear appropriate attire, especially gloves, eye protection and mask. Avoid contact with skin as it may cause irritation.

Cleaning:

Wash all the tools with water immediately after application.

Safety Instructions:

In the case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint from skin, use soap and water or appropriate cleanser. May be harmful if swallowed. In case of ingestion seek immediate medical attention. In the event of spillage, contain and collect spilt paint by using sand or earth.

Storage:

Store paint in a cool, dry and well ventilated place away from heat sources, flammables or direct sunlight. Keep container tightly closed in a secure, upright position. Do not store near food, drink or animal feed. Keep out of reach of children. Do not dispose of unwanted paint into drains, water sources or open sewers.

Shelf Life:

6 months from the date of manufacture in unopened original packing when stored in dry condition.

