



Colour-lock  
technology



Excellent  
Coverage



Dirt Pick-up  
Resistant



Anti-algal

**WEATHERBOND 8**



Water  
Resistance

**8**

Years  
Warranty\*



Heat Ban  
Technology



Quartz  
Technology



# THE 8 REVOLUTION

Introducing Weatherbond 8,  
best-in-class exterior emulsion with 8  
power packed features



**NO. 1 PAINT IN  
ASIA PACIFIC\***

\*T&C apply

**International quality, hi-tech paints**

**1800 425 3636 8939 65 3636**

## PRODUCT DESCRIPTION :

Nippon Paint Weatherbond 8 is a specially formulated acrylic based high performance exterior emulsion paint with **Quartz Technology** providing twice the toughness and durability resulting in supreme protection against harsh weather. It imparts a rich sheen finish and provides better anchoring and water resistance. It has anti-algal and dirt pick resistance to keep your walls fresh for longer time.




## PRODUCT FEATURES & BENEFITS :



### DIRT PICKUP RESISTANT

- The exteriors look new and beautiful for years
- It doesn't allow dirt/dust to settle on wall



### HEAT BAN TECHNOLOGY

- The innovative Heat Ban technology reflects back 90 % of the sunrays which reduces surface temperature up to 5°C
- This makes the interior cooler, thus helping to save energy used for Air conditioning



### QUARTZ TECHNOLOGY

- Hard and tough paint film
- It Provides excellent Water resistance, UV radiation and dirt penetration



### WATER RESISTANCE

- Prevents water to enter the walls hence forbidding algal or fungal growth
- Beautiful looking exteriors for long



### COLOUR-LOCK TECHNOLOGY

- Weatherbond 8 Keeps the walls looking beautiful for a long time



### Excellent Coverage


- This Product yields excellent coverage which might help save the total cost



### Low VOC

### LOW VOC

- It does not emit air polluting harmful vapours and paint odour that pollutes our environment
- Environment friendly and Healthy paint



### ANTI-ALGAL

- Weatherbond 8 is resistant to algae / fungus



### YEAR WARRANTY\*

(For Performance)

- \* **8 years Performance Warranty for Film Integrity, Flaking, Peeling & Colour Retention**
- \* **5 years Anti Algal warranty. Please refer Warranty Card for further details**

Where to Use : It Can be used on Exterior Masonry Surfaces

**International quality, hi-tech paints**

**1800 425 3636 8939 65 3636**

## PRODUCT TECHNICAL INFORMATION :

<b>Bases</b>	• White & Bases
<b>Colour Range</b>	• Please refer to Nippon Paint shade card and fan decks
<b>Finish</b>	• Rich Sheen finish
<b>Coverage</b>	• 110 - 130 sq.ft/litre/coat & 55 - 65 sq.ft/litre/2 coats (Actual coverage is dependant on the substrate Condition, surface porosity, method of application)
<b>Dry Time</b>	• To Touch: 30 minutes / To Recoat: 4-6 Hours
<b>Gloss Level</b>	• 60° head: 10 to 20 units
<b>Clean Up Solvent</b>	• Clean, potable water
<b>Stability of Dilute Paint</b>	• 24 Hours
<b>Shelf Life</b>	• 3 Years from the date of manufacture in original tightly closed containers
<b>Dilution</b>	• 40-50% by volume with clean, potable water



## Standard Application System :

Before application, read the safety, health and environmental information and the precautions given below

### Application Tool

Suitable for application by brush or roller or conventional spray

### Surface Preparation :

For Repainting : Clean the surface till it is free from dust, grease and flaking paint from surface. Any unstable paint to be removed, using high pressure wash or scraper whichever is appropriate. Algae And fungus on the wall to be removed, by using high pressure wash or coir brush, it must be treated with Walltron Kleanwall fungicidal solution.

New plaster/Fresh Concrete : Ensure surface is completely cured and dry. Application of cement paint/lime/Cement putty as undercoat is not recommended. Fill the cracks upto 3mm if any with Walltron N-seal crack fill powder.

## Recommended Painting System :

### Primer

- Nippon Dr. Bond Efflorescence Resistance Sealer
- Nippon Paint Multi-Purpose Wall Sealer/Exterior Primer
- Apply 1 coat and allow to dry for 4-6 hours

### Top Coat

- Nippon Weatherbond 8
- Apply 2-3 coats in an interval of 4-6 Hours

## Recommended Painting System For Waterproofing & Anticarbonation System :

### Base Coat

- Hydroschild Damp Proof
- Apply a coat with 30% dilution using potable water by volume
- Apply a coat without dilution

### Top Coat

- Nippon Weatherbond 8
- 2-3 coats with upto 20% dilution with potable water by volume at an interval of 4-6 hours

### Note :

For dark shades and Horizontal surface, one or two additional coats are recommended for better performance of paint film. Primed surface should be immediately painted with top coats. For best Performance use Nippon Dr. Bond Efflorescence Resistance Sealer as primer. If surface is applied with cement based putty apply Maxx clear Sealer as primer for superior adhesion.

## **Safety Health & Environmental Information :**

### **During Painting :**

- Always work in a well ventilated area
- Wear appropriate attire, especially gloves and eye protection gear
- Avoid contact with skin as it may cause irritation

### **Cleaning :**

- Wash all the tools with water immediately after application

### **Safety Instruction :**

- In the case of eye contact, rinse immediately with water and seek immediate medical treatment
- To remove paint from skin, use soap and water or appropriate cleanser
- In the event of spillage, contain and collect spilt paint by using sand or earth

### **Precautions :**

- Avoid painting when the temperature is below 10 degrees Celsius
- Painting is not recommended if the moisture content and alkalinity of the walls is high
- Moisture content of the walls should be below 16% (measured by Protimeter) and alkalinity of the wall should be below pH-9
- Relative humidity should be below 85%. Painting on a newly plastered wall is recommended after 12 weeks of curing

### **Storage :**

- Store paint in a cool, dry and well ventilated place away from heat sources, flammables or direct sunlight
- Keep container tightly closed in a secure, upright position
- Do not store near food, drink or animal feed
- Keep out of reach of children
- Do not dispose of unwanted paint into drains, water sources or open sewers
- To dispose safely, pour unwanted paint onto old newspapers and let dry before placing in a proper waste receptacle

### **Disposal Information :**

- Disposal of any paint waste & containers in accordance with applicable Environment (Protection) Act 1986 under the Hazardous Wastes (Management & Handling) rules 1989

### **Environment :**

- Does not contain any added lead, mercury or chromium compounds
- Lead content does not exceed 90 parts per million



## **Contact Us**

### **Registered Office : NIPPON PAINT (INDIA) PRIVATE LIMITED**

Plot No. K-8(I), Phase-II, SIPCOT Industrial Park, Mambakkam Village, Sriperumbudur, Sunguvarchatiram, Kancheepuram – 602 106, Tamil Nadu, India